



Enviro-Kote

SDS Number: 854

Revision Date: 5/17/2017

Page 1 of 9

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Environmental Sealer Supplies, LLC
 547 County Road E West
 St. Paul, MN 55126

Contact: Environmental Sealer Supplies, LLC
Phone: 651-797-4469
Email: info@essmn.com
Web: www.essmn.com

Product Name: Enviro-Kote
Revision Date: 5/17/2017
Version: 1
SDS Number: 854
CAS Number: MIXTURE
Chemical Family: Minerals
Chemical Formula: *** PROPRIETARY ***
Synonyms: Enviro-Kote
Product Use: Asphalt Sealcoat
Emergency Phone: 651-797-4469

2 HAZARDS IDENTIFICATION

NFPA:
 HMIS III:

Health = 1, Fire = 0, Reactivity = 0
 H*1/F0/PH0



HMIS III	
HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARDS	0
PERSONAL PROTECTION G Safety Glasses, Gloves, Vapor Respirator	

PERSONAL PROTECTION INDEX													
A		G											
B		H											
C		I											
D		J											
E		K											
F		X	Consult your supervisor or S.O.P. for "SPECIAL" handling directions										
A		n		O		p		q		r		S	
t		u		w		Y		Z		Additional Information			



Enviro-Kote

SDS Number: 854

Revision Date: 5/17/2017

Page 2 of 9

GHS Signal Word:

WARNING

GHS Hazard Pictograms:



GHS Classifications:

- Health, Skin corrosion/irritation, 2
- Health, Skin sensitization, 1
- Health, Serious Eye Damage/Eye Irritation, 2 A
- Health, Specific target organ toxicity - Single exposure, 3
- Health, Carcinogenicity, 2
- Health, Specific target organ toxicity - Repeated exposure, 2

GHS Phrases:

- H315 - Causes skin irritation
- H317 - May cause an allergic skin reaction
- H319 - Causes serious eye irritation
- H335 - May cause respiratory irritation
- H351 - Suspected of causing cancer
- H373 - May cause damage to organs through prolonged or repeated exposure

GHS Precautionary Statements:

- P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
- P262 - Do not get in eyes, on skin, or on clothing.
- P264 - Wash skin thoroughly after handling.
- P270 - Do not eat, drink or smoke when using this product.
- P271 - Use only outdoors or in a well-ventilated area.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- P302+352 - IF ON SKIN: Wash with soap and water.
- P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
- P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
- P333+313 - If skin irritation or a rash occurs: Get medical advice/attention.
- P337+313 - If eye irritation persists: Get medical advice/attention.
- P362 - Take off contaminated clothing and wash before reuse.
- P501 - Dispose of contents/container to an approved waste disposal plant.



Safety Data Sheet (SDS)

Environmental Sealer Supplies, LLC

Enviro-Kote

SDS Number: 854

Revision Date: 5/17/2017

Page 3 of 9

3

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Percentage	Chemical Name
1317-65-3	37.5-58.5%	Proprietary, non-hazardous, non-regulated**
8052-42-4	20-30%	Asphalt
14808-60-7	20-30%	Silica, crystalline quartz
1333-86-4	1-2%	Carbon black
2634-33-5	<0.5%	1,2-Benzisothiazol-3(2H)-one

**Balance of ingredients are non-hazardous, as defined by OSHA 29CFR1910.1200 or the Globally Harmonized System of Classification and Labeling of Chemicals (GHS), or hazardous in less than 1% concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory/skin sensitizers).

4

FIRST AID MEASURES

- Inhalation:** Give oxygen or artificial respiration if needed. If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
- Skin Contact:** Promptly flush skin with water for several minutes to ensure all chemical is removed. If reddening develops and/or persists, obtain medical attention. If reddening and/or a rash develops and/or persists, obtain medical attention.
- Eye Contact:** Flush with large amounts of water for at least 15 minutes, lifting upper and lower lids occasionally. If irritation persists, obtain medical attention.
- Ingestion:** Rinse mouth with water. Give 3-4 glasses of water or milk to dilute stomach contents. Do NOT induce vomiting. If vomiting occurs, give more water or milk. Never give anything by mouth to an unconscious person. If irritation develops and/or persists, seek medical attention

Most important symptoms and effects, both acute and delayed:

The most important known symptoms and effects are described in the labelling (see Section 2) and/or Section 11. Prolonged inhalation of Silica, crystalline quartz may result in silicosis. Silicosis is a disabling pulmonary fibrosis characterized by fibrotic changes and miliary nodules in the lungs and may be accompanied by a dry cough, shortness of breath, emphysema, decreased chest expansion, and increased susceptibility to tuberculosis. In advanced stages, loss of appetite, pleuritic pain, and total incapacity to work may occur. Advanced silicosis may result in death due to cardiac failure or destruction of lung tissue. Silica, crystalline quartz is classified as Group 1 "Known to be carcinogenic to humans" by the IARC and "Sufficient evidence" of carcinogenicity by the NTP. The chronic health risks are associated with respiring particles of 3-4 microns over protracted periods of time. Currently, there is a limited understanding of the mechanisms of crystalline silica toxicity, including its mechanisms for lung carcinogenicity. Additional studies are needed to determine whether the cell transforming activity of quartz is related to its carcinogenic potential.

Indication of any immediate medical attention and special treatment needed:

No data available.

5

FIRE FIGHTING MEASURES

- Flammability:** Not flammable
- Flash Point:** None
- Flash Point Method:** DNA
- Burning Rate:** No data available
- Autoignition Temp:** No data available



Enviro-Kote

SDS Number: 854

Revision Date: 5/17/2017

Page 4 of 9

LEL: None
UEL: None

Extinguishing Media:

Water Spray
 Carbon Dioxide
 Alcohol-Resistant Foam

Special Hazards Arising From the Substance or Mixture:

Oxides of Aluminum, Carbon, Nitrogen (NOx), Silicon, Sodium, Sulfur and Titanium.
 Unburnt hydrocarbon particulate.
 Trace quantities of Hydrogen Sulfide.
 Temperatures above 870 °C may cause Tridymite to form.
 Temperatures above 1470 °C may cause Cristobalite to form.

Advice for Firefighters:

Firefighters should wear full-face, positive-pressure respirators.

Further Information:

If incinerated, may release toxic fumes.
 Small quantities of Hydrogen Sulfide may be released upon heating. Use caution.
 Exercise care when using water to extinguish fires, as hot asphalt products may produce steam and violent foaming.
 See Section 7 for more information on safe handling.
 See Section 8 for more information on personal protection equipment.
 See Section 13 for disposal information.

6

ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Use personal protective equipment, including vapor respirator when handling aqueous product.
 Avoid breathing vapors.
 Avoid creation of aerosols.
 Keep from contacting skin or eyes.
 Ensure adequate ventilation.
 Evacuate personnel to safe areas.

Environmental precautions:

Prevent further release (leakage/spillage) if safe to do so.
 Do not allow product to enter drains.
 Do not allow to drain to environment.

Methods and materials for containments and cleaning up:

Absorb with liquid-binding material (sand, diatomite, universal binders, sawdust).
 Place contaminated material into suitable, closed containers for disposal.
 Dispose of contaminated material according to Section 13.
 After spillage has been collected, area may be flushed with water or wet-brushed.
 Ensure adequate ventilation.

Reference to other sections:

Comply with federal, state and local regulations on reporting spills.
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for information on proper disposal.



Enviro-Kote

SDS Number: 854

Revision Date: 5/17/2017

Page 5 of 9

7

HANDLING AND STORAGE

Handling Precautions:

Avoid breathing vapors or mist.
 Avoid contact with eyes, skin, or clothing.
 Keep containers closed when not in use.
 Do not expose containers to open flame or excessive heat.
 Do not puncture or drop containers.
 Handle with care and avoid spillage on the floor.
 Keep material out of reach of children.
 Keep material away from incompatible materials.
 Wash thoroughly after handling.
 Ensure adequate ventilation.

Storage Requirements:

Keep away from heat, sparks and flames.
 Store in a dry area.
 Store away from strong acids, strong bases, strong oxidizing agents, strong reducing agents and Hydrogen Fluoride.

8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use local exhaust at filling zones and where leakage and dust formation is probable. Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

Personal Protective Equip:

Eye/face protection:

When using material use safety glasses, gloves and vapor respirator according to HMIS PP, G. All safety equipment should be tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EU).

Skin protection:

Handle with gloves made from water-impermeable materials. Barrier creams should not be used in place of gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact. Dispose of contaminated gloves according to applicable laws and laboratory practices.

Body Protection:

Chemically resistant gloves and safety glasses are recommended. Type of protective equipment should be selected based on concentration amount and conditions of use of this material.

Respiratory protection:

Use of a combined vapor respirator is recommended. A full-face dust/vapor respirator may be required as backup to engineering controls when proper engineering controls are not in place to keep TLV and PEL limits below defined thresholds. All respiratory equipment must either be NIOSH/MSHA-approved (under 30 CFR 11) or NIOSH-approved (under 42 CFR 84).

Control of environmental exposure:

Prevent leakage or spillage if safe to do so. Do not let material enter drains.

Components with workplace control parameters:

Component(s): Asphalt



Safety Data Sheet (SDS)

Environmental Sealer Supplies, LLC

Enviro-Kote

SDS Number: 854

Revision Date: 5/17/2017

Page 6 of 9

CAS No(s): 8052-42-4
USA ACGIH (TWA/TLV): 0.025 mg/m³

Component(s): Silica, crystalline quartz
CAS No(s): 14808-60-7
USA ACGIH (TWA/TLV): 0.025 mg/m³
USA OSHA (TWA/PEL, General Industry): 30 mg/m³ (%SiO₂+2, Total Dust, 8 hours)
USA OSHA (TWA/PEL, General Industry): 10 mg/m³ (%SiO₂+2, Respirable Fraction, 8 hours)
USA OSHA (TWA/PEL, General Industry): 250 mppcf* (%SiO₂+5)
USA OSHA (TWA/PEL, Construction Industry): 250 mppcf* (%SiO₂+5)
USA OSHA (TWA/PEL, Shipyard Employment): 250 mppcf* (%SiO₂+5)

Component(s): Carbon black
CAS No(s): 1333-86-4
USA ACGIH (TWA/TLV): 3.0 mg/m³
USA OSHA Occupational Exposure Limits Table Z-1 Limits for Air Contaminants (TWA): 3.5 mg/m³
USA NIOSH (TWA/REL): 0.1 mg/m³

*mppcf = Millions of particles per cubic foot of air

Biological occupational exposure limits:

Contains no substances with biological occupational exposure limits values.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Brown Slurry	Odor:	Asphalt
Physical State:	Liquid	Molecular Formula:	MIXTURE
Odor Threshold:	Not determined	Solubility:	Appreciable
Particle Size:	Not determined	Softening Point:	Not determined
Spec Grav./Density:	Not determined	Percent Volatile:	< 40%
Viscosity:	Not determined	Heat Value:	Not determined
Sat. Vap. Conc.:	Not determined	Freezing/Melting Pt.:	Not determined
Boiling Point:	Not determined	Flash Point:	DNA
Flammability:	(solid, gas): Not flammable	Octanol:	Not determined
Partition Coefficient:	Not determined	Vapor Density:	(air = 1): Water
Vapor Pressure:	(mm Hg @ 20 °C): Water	VOC:	Not determined
pH:	@ 100%: 8.0 - 9.5	Bulk Density:	Not determined
Evap. Rate:	(n-Butyl Acetate = 1): Not determined	Auto-Ignition Temp:	Not determined
Molecular weight:	MIXTURE	UFL/LFL:	None
Decomp Temp:	Not determined		

10 STABILITY AND REACTIVITY

Stability:	Product is stable under normal conditions.
Conditions to Avoid:	Incompatibilities, flames, ignition sources.
Materials to Avoid:	Strong acids, strong bases, strong oxidizing agents, strong reducing agents and Hydrogen Fluoride.
Hazardous Decomposition:	Oxides of Aluminum, Carbon, Nitrogen (NO _x), Silicon, Sodium, Sulfur and Titanium. Unburnt hydrocarbon particulate. Trace quantities of Hydrogen Sulfide.



Enviro-Kote

SDS Number: 854

Revision Date: 5/17/2017

Page 7 of 9

Temperatures above 870 °C may cause Tridymite to form.
 Temperatures above 1470 °C may cause Cristobalite to form.

Hazardous Polymerization: Will not occur.

11

TOXICOLOGICAL INFORMATION

Component(s): Asphalt; Silica, crystalline quartz; Carbon black; 1,2-Benzisothiazol-3(2H)-one

CAS No(s): 8052-42-4; 14808-60-7; 1333-86-4; 2634-33-5

Acute Toxicity:

LD50 Oral - Rat: 500 mg/kg

LD50 Dermal - Rabbit: > 2,000 mg/kg

LC50 Inhalation - Rat: 0.371 mg/l

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Eye Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitation: May cause allergic reactions in certain sensitive individuals (1,2-Benzisothiazol-3(2H)-one).

Germ Cell Mutagenicity: No data available

Carcinogenicity: This product is or contains a component that is classifiable as to its carcinogenicity to humans (Silica, crystalline quartz), and two components that are classifiable as possibly carcinogenic to humans (Asphalt, Carbon black) based on their IARC, ACGIH, NTP or OSHA classifications. Limited evidence of carcinogenicity in human studies.

IARC: 1 - Group 1: Carcinogenic to humans (Silica, crystalline quartz); 2B - Group 2B: Possibly carcinogenic to humans (Asphalt, Carbon black).

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: Known to be a human carcinogen (Silica, crystalline quartz).

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive Toxicity: No data available

Specific Target Organ Toxicity - Single Exposure: No data available

Specific Target Organ Toxicity - Repeated Exposure: Inhalation - May cause damage to organs through prolonged or repeated inhalation exposure when handling dried material (Silica, crystalline quartz).

Aspiration Hazard: No data available

Additional Information:

Component: Asphalt; RTECS: CI9900000

Component: Silica, crystalline quartz; RTECS: VV7330000

Component: Carbon black; RTECS: FF5800000

Component: 1,2-Benzisothiazol-3(2H)-one; RTECS: DE4620000



Enviro-Kote

SDS Number: 854

Revision Date: 5/17/2017

Page 8 of 9

12**ECOLOGICAL INFORMATION**

Component(s): Asphalt; Silica, crystalline quartz; Carbon black; 1,2-Benzisothiazol-3(2H)-one
CAS No(s): 8052-42-4; 14808-60-7; 1333-86-4; 2634-33-5

Toxicity:*Toxicity to fish:*

LC50 - Oncorhynchus mykiss (Rainbow Trout): 0.8 mg/l (96 h)

Toxicity to daphnia and other aquatic invertebrates:

EC50 - Daphnia magna (Water Flea): 4.4 mg/l (96 h)

Persistence and Degradability:

No data available.

Bioaccumulative potential:

No data available.

Mobility in Soil:

No data available.

Results of PBT and vPvB assessment:

Not required/conducted.

Other Adverse Effects:

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life.

13**DISPOSAL CONSIDERATIONS**

Product: Hazardous wastes shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution, release into the environment or damage to people and animals. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated Packaging: Dispose of as unused product.

14**TRANSPORT INFORMATION****DOT (US)**

Non-Regulated, Water Based Asphalt Emulsion

IMDG

Non-Regulated, Water Based Asphalt Emulsion

IATA

Non-Regulated, Water Based Asphalt Emulsion



Enviro-Kote

SDS Number: 854

Revision Date: 5/17/2017

Page 9 of 9

15

REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Asphalt (8052424 20-30%) MASS, NJHS, NRC, PA, PROP65, SARA311/312, TSCA, TXAIR

*Silica, crystalline quartz (14808607 20-30%) MASS, NJHS, NRC, OSHAWAC, PA, PROP65, SARA311/312, TSCA, TXAIR

*Carbon black (1333864 1-2%) MASS, NJHS, OSHAWAC, PA, PROP65, SARA311/312, TSCA, TXAIR

*1,2-Benzisothiazol-3(2H)-one (2634335 <0.5%) NJHS, PA, SARA311/312, TSCA

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List
 NJHS = New Jersey Right to Know Hazardous Substances
 NRC = Nationally Recognized Carcinogens
 OSHAWAC = OSHA Workplace Air Contaminants
 PA = PA Right-To-Know List of Hazardous Substances
 PROP65 = CA Prop 65
 SARA311/312 = SARA 311/312 Toxic Chemicals
 TSCA = Toxic Substances Control Act
 TXAIR = TX Air Contaminants with Health Effects Screening Level

16

OTHER INFORMATION

Disclaimer:

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that Environmental Sealer Supplies, LLC believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of Environmental Sealer Supplies, LLC control, Environmental Sealer Supplies, LLC makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.

Preparation Information:

GHS Conversion Services
 www.ghsconversionservices.com
 (414) 336-2546